EXLON-Fluoro Resin Series EXLON PFA Tubing







These tubing have excellent heat resistance, chemical resistance, weather resis-Characteristics tance, non-cohesiveness, and electric insulation. These tubing can be used for a variety of purposes, including semiconductor production devices, chemical plants, physiochemical devices, food manufacturing equipment, and medical devices.



Highly heat resistant

These tubing are made of PFA resin with the heat resistance which allows continuous uses up to 260°C.



Chemical resistance

These tubing are resistant to and inactive against most chemicals and solvents.



Weather resistant

They have properties that resist age-dependent changes and deteriorations in harsh outdoor environments.



Non-cohesive property

These tubing do not adhere on sticky objects and can be easily peeled off.



Electric insulation

These tubing have excellent electrical properties and the highest insulation resistance in plastic.

PFA Tubing

ІШЯУЕ









EXLON PFA Tubing

Standard size chart							
Size	Dimension to	lerance (mm)	Unit length (m)				
$(Outer diameter \times Inner diameter)$	Outer diameter	Thickness	2 straight	10	20	50	100
3×2	±0.1	±0.08		•	•		•
4 × 2	±0.1	±0.08		•	•		
4×2.5	±0.1	±0.08		•	•		
4×3	±0.1	±0.08		•			
5 × 4	±0.1	±0.08		•			•
6×4	±0.1	±0.08		•	•		
6×5	±0.1	±0.08		•			
7×6	±0.1	±0.08					
8×6	±0.1	±0.08		•			
8×7	±0.1	±0.08		•			
9×8	±0.1	±0.08					
10×8	±0.1	±0.08					
10×9	±0.1	±0.08		•			
12×9	±0.1	±0.08		•			
12×10	±0.1	±0.08					
16×13	±0.1	±0.08		•			
16×14	±0.1	±0.08		•			
18×16	±0.1	±0.08		•			
19×16	±0.1	±0.08					
3.17×1.59	±0.1	±0.08		•			
6.35×3.96	±0.1	±0.08					
6.35×4.35	±0.1	±0.08					•
9.53×6.35	±0.1	±0.08					•
9.53×7.53	±0.1	±0.08					
12.7×9.53	±0.1	±0.08					•
12.7×10.7	±0.1	±0.08					
19.05×15.88	±0.1	±0.08					•
25.4×22.26	±0.15	±0.08	•	•	•	•	•

Ones marked with "
" means they are in stock.

- Availability of inventory may change, because they are based on the production at this point.
- Other sizes and lengths besides the standard lengths can be produced. Please contact us for details.

